TECHNICAL DATA SHEET



BOPP Carton Box Sealing Tape 100

❖ PRODUCT APPLICATIONS

- ✓ Non-critical of light weight carton
- ✓ Stationery & light sealing performance



❖ PRODUCT STRUCTURE

Total Thickness	40 μm	
Film	Biaxially Oriented Polypropylene	
Adhesive	Water Base Acrylic Adhesive	
Colour ⁽¹⁾	Clear and Tan	

⁽¹⁾ Contact your VISKO sales representative for other available colour or customized matching colours.

❖ SIZE AVAILABILITY⁽²⁾

JUMBO ROLL	FINISHED ROLL			
1280mm (W) X 6000m (L)	STANDARD WIDTH, mm	36, 48, 60, 72		
1610mm (W) X 6000m (L)	STANDARD LENGTH, m	50, 80, 90, 100, 900, 1000		
(2) Contact your VISKO sales representative for other available sizes				

❖ PHYSICAL PROPERTIES

Test Item		Typical Result ⁽⁴⁾	Testing method
Total Thickness ⁽³⁾ (µm)		40	PSTC 133
180° Peel Adhesion, (gf/2	5mm)	515	PSTC 101
Holding Power (Hours)		50	PSTC 107
Initial Ball Tack (mm)		30	PSTC 6
Tensile Strength, (kg/mm²)	MD	12.8	PSTC 131
	TD	18.0	
Elongation at Break, (%)		132	PSTC 131

⁽³⁾ Total thickness allowance ±1μm

❖ STORAGE CONDITION

The tape should be stored in its original packaging in a cool, dry area and away from direct sunlight, temperature at 5-26°C, Relative Humidity 40-60 %.

SHELF LIFE

To obtain best performance, use this product within 18 months from the date of manufacture.

❖ USAGE CONDITION

Surfaces to which the tape is applied should be clean, dry and free of grease, oil or contaminants

Important Notice to Purchaser

All properties are approximate and are based on tests believed to be reliable and performed in conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. It is suggested that purchasers should test, prior to use, the suitability of this product for their particular application.

⁽⁴⁾ The typical result were collected from the average result of series of tests, it is not the product specification.